## Intertecnica 6250 RH 3 Point Fastener 72mm-80mm

PART No: IN6250RH-80

## **FEATURES**

Intertecnica 6250 Right Hand 3 Point Fastener with Lock, to suit 72mm - 80mm Panel Thickness

## Features:

- Easy-to-use lever action with adjustable strikes provides a positive seal by compressing the gasket along 3 points.
- For overlapping doors.
- European design & Styling
- Stainless Steel lever Handles
- Constructed from Industrial Grade Composited materials for strength and resistance from corrosion
- Suitable for both negative & positive temperatures -40/40 °C
- Inside release handle with Photoluminescent arrows
- Invisible & Tamperproof fixings
- Soft & quiet operation
- Lockable
- No reinforcement is needed in the door leaf panel
- Includes luminous internal & external Arrow Labels.
- Max recommended door weight: 100kg
- Door height: 500mm 3000mm
- Door width: 500mm 2000mm
- Door panel thickness: 72mm 80mm
- Door offset: 72mm 120mm
- Right hand opening.

This Latch kit excludes the Connecting Rod between the latch and strikes. The manufacturer recommends that a Stainless Steel flat bar  $20 \text{mm} \times 3 \text{mm}$  thick is used.

Combine this latch set with Intertecnica's IN2830RV Hinge, which offers a non-lift-off hinge and tamper-proof fixings for added security.

CRH & All manufacturers highly recommend that all internal safety release mechanisms fitted to doors are checked at least 3 times weekly to ensure they are functioning correctly.

## **ADDITIONAL INFORMATION**

The Intertecnica 6000 series Fasteners are also available as a Single-point fasteners system. These products are listed under Latches & Strikes in our Refrigeration & Cold Storage Hardware section.







info@crh.com.au

www.crh.com.au