

KL200 Zip Clip

PART No: KL200

FEATURES

KL200 Zip Clip, For 4.8mm Cable. 300kg Weight Rating.

Faster

Zip-Clip Cable Locks and Galvanised Looped Cable are the fast & versatile way to suspend insulated panels. Studies have shown installation time can be reduced up to 6 times compared to traditional chain and other cable systems.

Industry Tested and Approved

Our complete system from cable, Zip-Clip to CRH Suspension Components have been thoroughly tested in NATA Accredited laboratories in Melbourne. Approved by all major panel manufacturers, our solution is fully compliant with the Insulated Panel Council of Australasia (IPCA) code of Practice

Engineered Solutions

Zip-Clip locking devices are manufactured from a Zamak 5 zinc alloy main body with an internal stainless-steel spring and sintered steel locking wedges. They offer a 300 kg SWL. Zip-Clip Galvanised Loop Cables with factory swagged loop termination are manufactured under strict quality-controlled conditions. They are specifically designed to be used in conjunction with the KL200 Locking device. This standard system utilises premium grade galvanised mild steel electro-galvanised wire rope manufactured to BS EN 12385

CRH Suspension Components

With options of M10 or M12 kits to suit panel and wall thickness of 75mm, 100mm, 150mm, 200mm and 250mm panel. Kits are supplied in HDG and include M10 or M12 threaded rod, nuts, L-shaped A70 Bracket and M10 or M12 Mushroom Cap.

Colour: Grey

Material: Pressure Die-Cast Zinc & Stainless Steel.

ADDITIONAL INFORMATION

KL200's are designed for use with 4.8mm (3/16") wire cable. It has a weight rating of 300kg with a Safe Working Load Factor of 5:1. Typical applications include; Ceiling Suspension Systems, heavy Cable Trays, Signs & Sound Systems.



CRH Australia Pty Ltd 1-3 Nelson Street Moorabbin VIC 3189 Australia t+61 3 9532 f+61 3 9532 2696



info@crh.com.au

www.crh.com.au